

## SR15 SpeedRail



### Overview

15mm high top hat rail in powder-coated aluminium. Designed to be fixed directly to steel beam flanges of up to 12mm thick using CS18 bimetallic tek screws. Used with self-tapper screws and clips.

This product must be fully supported underneath, it is not designed to bridge gaps in steelwork.

### INSTRUCTIONS FOR USE:

1. Clear steelwork of any obstructions on the surface, and lay SpeedRails onto the top flanges.
2. Using a string-line or a decking board, ensure the SpeedRails are aligned. Clamp them in position, butting SpeedRails tightly together to ensure accurate deck board spacing.
3. SpeedRails may be cut to length and SpeedRail end clips rivetted to drilled positions to hold boards in position. End clips are provided in secret fix half-height format to engage with the edge groove of boards or full height format where boards need to be cut and do not have an edge groove.
4. Using bi-metallic Tek screws provided, fix the SpeedRails in position, using a minimum of 4no screws per rail, ideally in a zig-zag fashion.
5. Fix boards using edge clips as normal, using provided self-tapper screws in lieu of Tek screws normally provided with clips.

### DIMENSIONS:

Height	15mm
Overall width	63mm
Supplied length	2.5m
Joist securing holes	5.5mm

Continued over...



MyDeK Ltd, Granville House, Stockenchurch, HP14 3BG

T: +44 (0)3300 94 94 11

E: [sales@mydek.com](mailto:sales@mydek.com)

[www.mydek.com](http://www.mydek.com)

---

## MATERIAL PROPERTIES:

Grade	Aluminium 6063 T6
Thickness	1.5mm
Finish	Powdercoated black RAL 9005
Item Code	<b>SR15.2500.9005</b> (2.5m length)

---

## ACCESSORIES:



CS18 stainless steel (A4) hex Tek Screw for steel flanges of up to 12mm



SC01 Secret fix end clips for grooved board edges



SC02 Full height end clips for cut board edges



RB01 Rivets to fix end clips to the SpeedRail

For full range of accessories visit [www.mydek.com](http://www.mydek.com)



MyDek Ltd, Granville House, Stockenchurch, HP14 3BG

T: +44 (0)3300 94 94 11

E: [sales@mydek.com](mailto:sales@mydek.com)

[www.mydek.com](http://www.mydek.com)